



* End spacing dimension is equal at both ends based on customer specified length.

DIMENSIONS (in.)

Guide Roller Size	Width	Height	Mounting Shoulder Location	Mounting Shoulder to Center Line	Mounting Shoulder Depth	Hole to Hole Spacing	Hole Size (Diameter)	Mounting Hole Location	Weight Per Foot (Lbs.)
SIZE	TW	TH	TE	MO	SH	HSP	HD	MHL	
T-1	0.437	0.187	0.125	0.031	0.062	2.000	0.156	0.156	0.18
T-2	0.625	0.250	0.187	0.031	0.094	3.000	0.203	0.219	0.34
T-3	0.875	0.343	0.250	0.062	0.109	3.000	0.281	0.313	0.69
T-4	1.062	0.437	0.312	0.093	0.125	4.000	0.344	0.375	1.10

SPECIFICATIONS & OPTIONS

- Cut to length tolerance $\pm .063$ ".
- Hole spacing and size tolerance is $\pm .005$ ".
- V-edge is case hardened to 55+ Rc.
- Track is available undrilled or pre-drilled and cut to length.
- Track can be ordered with corrosion resistant options:
Black Oxide, Electroless Nickel, Nedox.
- Track can be All dimensions are industry standard ($\pm .005$ inches), unless otherwise specified.

MATERIALS

- Track material is 1045.
- Stainless Material is 420 SS, designated by - SS.

NOMENCLATURE

SINGLE TRACK T D - 2 SS - 1263 - 5

Track Drilled Size Length (12.63") Holes Stainless Steel