



PART #	# OF HOLES	A ± 0.003	B	C	D	E
TD-1 - 1250 - 7	7	12.50				
TD-1 - 2450 - 13	13	24.50				
TD-1 - 3650 - 19	19	36.50				
TD-1 - 4850 - 25	25	48.50				
TD-1 - 6050 - 31	31	60.50	0.250	2.000	0.156	0.156
TD-1 - 7250 - 37	37	72.50				
TD-1 - 8450 - 43	43	84.50				
TD-1 - 9650 - 49	49	96.50				
TD-2 - 1263 - 5	5	12.63				
TD-2 - 2463 - 9	9	24.63				
TD-2 - 3663 - 13	13	36.63				
TD-2 - 4863 - 17	17	48.63				
TD-2 - 6063 - 21	21	60.63	0.310	3.000	0.203	0.219
TD-2 - 7263 - 25	25	72.63				
TD-2 - 8463 - 29	29	84.63				
TD-2 - 9663 - 33	33	96.63				
TD-3 - 1275 - 5	5	12.75				
TD-3 - 2475 - 9	9	24.75				
TD-3 - 3675 - 13	13	36.75				
TD-3 - 4875 - 17	17	48.75				
TD-3 - 6075 - 21	21	60.75	0.380	3.000	0.281	0.313
TD-3 - 7275 - 25	25	72.75				
TD-3 - 8475 - 29	29	84.75				
TD-3 - 9675 - 33	33	96.75				
TD-4 - 1300 - 4	4	13.00				
TD-4 - 2500 - 7	7	25.00				
TD-4 - 3700 - 10	10	37.00				
TD-4 - 4900 - 13	13	49.00				
TD-4 - 6100 - 16	16	61.00	0.500	4.000	0.344	0.375
TD-4 - 7300 - 19	19	73.00				
TD-4 - 8500 - 22	22	85.00				
TD-4 - 9700 - 25	25	97.00				

NOMENCLATURE

SINGLE TRACK T D - 2 SS - 1263 - 5
Track Drilled Size Stainless Steel Length (12.63") Holes

- All dimensions are industry standard (± .005 inches), unless otherwise specified.
- Standard drilled track also available in stainless steel.